



Features

- High performance & cost effective
- Wide input range (100-1240V ~50/60Hz)
- Output 12Vdc @ 1.5A
- 3 pole AC inlet IEC320-C14
- Compliance UL/CUL/TUV/BSMI/CB/FCC/CE/N10467
- LED power indication
- Supports all ProLinx products
- Compact & rugged design 93mm(L) x 54mm(W) x 36mm(H)

Description

The PS-1200 is a universal input power supply with a 2M IEC power lead provided as standard. Other plugs are available upon request. The PS-1200 is compatible with all ProLinx products.

Specifications

Safety Standards	UL60950-1, CSA C22.2, TUV EN60950-1, BSMI CNS14336
EMI Conduction & Radiation	EN55022 CLASS B, FCC PART 15 / CISPR22 class B, CNS13438 class B
Ripple & Noise (max)	80mVp-p
Voltage Regulation	+/-3.0%
Line Regulation	+/-3.0%
Efficiency (typical)	81%
MTBF	500Khrs (min)
Additional specifications are available upon request.	

Accessories (included)

Power lead, SAA approved, 2M, IEC320-C14 connector

Compatibility

Compatible with all SBC ProLinx products

Compliances

CE; UL; C-Tick
RoHS Compliant Directive 2002/95/EC

Ordering Information

- PSLV-1200 240V AC / 12V DC power supply

Copyright by SBC 2008. Product Specifications are subject to change without prior notice.